

SCREEN SHARING

Power supply voltage:

- 6 - 24V.

Ambient operating temperature:

- -20 to 60°C.

Storage temperature:

- -30 to 90°C.

Size:

- 202 x 108 mm.

Fixing:

- 4 x M5 thread insert.

Display:

- 5 inches.
- 800 RGB (H) X 480 (V).
- Transmissive a-Si TFT.
- Weight - 400 gr.

TFT can display following information:

- Speed.
- Tachometer.
- Fuel/SoC.
- Gear.
- Battery voltage.
- Odometer.
- Trips.
- Clock.
- Ambient temperature.
- Coolant temperature.
- Drive mode and any additional available vehicle information.
- Navigation map of the smartphone.

Communication:

- CAN bus line (standard) - Speed up to 1000 Kbit/s.

Connectivity:

- Wi-Fi 802.11b/g/n.
- Dual-mode Bluetooth v4.2.

Indicators:

- Winkers L.
- High beam.
- General failure.
- ABS.
- TC.
- Alarm.
- MIL.
- Oil pressure.
- Cruise control.
- Winkers R.
- As optional, customizable dial.

General features cluster:

- Share the navigation map of the smartphone. Combine it with any graphics in the TFT.
- Receive smartphone notifications like calls, SMS or social networks.
- APP needed or mobile SDK available (iOS and Android).

General features APP:

- Navigation map.
- Customize the instrument cluster (color, language, etc.).
- Receive telemetry data of the motorbike (trip distance, fuel level, etc.).

As optional features:

- 7 inches display (1280x768).
- App development.
- USB for charging.
- GPS and GPRS - Connectivity box needed.

